
QTY -3	P/N	DESCRIPTION
Х	D2362-3	STEP SUPPORT BRACKET
1	D2265	STEP SUPPORT CASTING
1	D2397-1	RUBBER CUSHION
1	D2397-3	RUBBER CUSHION



# HOLE WITH SLOT AND BOND WITH CONTACT CEMENT PER MANUFACTURER'S SPECIFICATION D2397-1 RUBBER CUSHION D2397-3 RUBBER CUSHION-ENGRAVE "D2362-3 REV. G" 6 D2362-3 REV. G FACE SURFACE 0.250 x 1.285 WITH MAX DEPTH OF 0.020 **DETAIL B**

D

С

В

2

CENTER D2397-1/-3 RUBBER

REV.	DESCRIPTION		DATE
Α	NEW ISSUE	BW	95.02.15
В	CHANGED RUBBER TO D2397	BW	95.03.22
С	ADD D2362-5	BW	96.01.22
D	ADD D2362-7		97.05.21
Ε	REDRAWN, ADD D2397-5	CP	98.12.04
F	UPDATE D2362-3 TO ADD SLOT COUNTERBORE AND ADJUSTED SLOT SIZE, WAS 1.200 x1.000 IS 1.400 x 1.00, AND ADDED ENGRAVE PART# AND REV. UPDATED TO CURRENT STANDARDS. REASON CAR19-305		19.12.09
G	ADD "FACE SURFACE" ON DETAIL B, AND AJUSTED VIEWS FOR CLARITY		20.02.19

DESIGN	SAD	DART AEROSPACE	LTD
DRAWN	SAD	HAWKESBURY, ONTARIO, CANA	ADA
CHECKED	RF	DRAWING NO.	REV. G
MFG. APPR.	DD	D2362	SHEET 1 OF 3
APPROVED	NO	TITLE	SCALE
DE APPR.	CP 4	STEP SUPPORT BRACKE	T NTS
DATE		COPYRIGHT © 1995 BY DART AEROSPAC	E LTD

## D2362-3 STEP SUPPORT BRACKET

D

NOTES:
1) MATERIAL: MAKE FROM D2265
2) FINISH: POWDER COAT "WHITE" (4.3.5.1) PER DART QSI 005 4.3 BEFORE BONDING
3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
4) UNITS: INCHES UNLESS OTHERWISE NOTED
5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
6) IDENTIFICATION: IDENTIFY PER DART QSI 044 6.3 WITH 0.13 HIGH LETTERS, 0.010 DP, AND R0.010 MIN TOOL RAD

7) WEIGHT: 0.86 lbs

RELEASED

2020 MAY 06 P


**APPROVED** 20.02.19

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS


3


8

5



3.750 REF






D


С

В

#### **D2362-7 STEP SUPPORT BRACKET**



2



### D2362-041 PRE-FLIGHT STEP

#### NOTES:

D

С

- 1) MATERIAL: MAKE D2362-7 FROM D2265 CASTING
- 2) FINISH: POWDER COAT "WHITE" (4.3.5.1) PER DART QSI 005 4.3

APPLY BLACK ANTI-SKID PAINT TO TOP SURFACE OF STEP PER QSI 005 4.4

- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER DART QSI 044 6.1
- 7) WEIGHT: 1.18 lbs
- 8) WELD PER DART QSI 004

8

RELEASED 2020 MAY 06 4

DESIGN	SAD
DRAWN	SAL
CHECKED	RF
MFG. APPR.	DD
APPROVED	NO
DE APPR.	CP
DATE	

DESIGN	SAD	
DRAWN	SAD	
CHECKED	RF	
MFG. APPR.	DD	Į
APPROVED	NO 2	7
DE APPR.	CP (	,
DATE 20.0	2 19	

DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA		
DRAWING NO.	REV. G	
D2362	SHEET 3 OF 3	
TITLE	SCALE	

STEP SUPPORT BRACKET NTS

3

5